

# Material Safety Data Sheet (MSDS)

**Emergency Contact:**

Name:	YHI Power Pty Ltd
Address:	20-22 Venture Way, Braeside, VIC 3195
Website:	<a href="http://www.yhipower.com.au">www.yhipower.com.au</a>
Phone number:	+61 03 9588 1888 / 0413 381 228
Email address:	<a href="mailto:inquiry@yhipower.com.au">inquiry@yhipower.com.au</a>

Data Sheet No: VRLA AGM Issue 7

Date Issued: 23rd February 2023

## 1 Identification of the substance

Product name: Sealed Lead Acid Battery

Trade name: Lead acid battery

Distributor: YHI POWER PTY LTD

Address: 20-22 Venture Way, Braeside VIC 3195

Website: [www.yhipower.com.au](http://www.yhipower.com.au)


Tel: 03 9588 1888 / 0413 381 228

Email: [inquiry@yhipower.com.au](mailto:inquiry@yhipower.com.au)


## 2 Hazards Identification

Classification of the substance or mixture according to Regulation (EC) No 1272/2008 [CLP/GHS]  
Material is an article. No health effects are expected during normal use of this product as sold. Hazardous exposure may occur when the product is heated, oxidized or otherwise processed, damaged or subjected to misuse. Follow manufacturer's instructions for installation, service and use.

### Health


GHS code	Hazard class/category		Hazard statements	2008/98/EC code	Labels
H302	Acute Toxicity (Oral)	Category 4	Harmful if swallowed	HP 6	
H314	Skin corrosion	Category 1A	Causes severe skin burns and eye damage	HP 8	
H335	Specific target organ toxicity, single exposure, Respiratory tract irritation	Category 3	Might cause respiratory irritation	HP5	
H361	Reproductive toxicity	Category 2	Suspected damaging of fertility or the unborn child	HP 10	

## Environment

GHS code	Hazard class/category		Hazard statements	2008/98/EC code	Labels
H 411	Hazardous to the aquatic environment, acute hazard	Category 2	Toxicity to aquatic life with long lasting effect	HP 14	

## Physical

Under abnormal use in not ventilated rooms may form explosive air/gas mixture during charging or when extreme overcharging / Extremely flammable gas (hydrogen) / Explosive, fire, blast or projection hazard.

GHS code	Hazard class/category		Hazard statements	2008/98/EC code	Labels
H203	Explosives	Division 1.3	Explosive; fire, blast or projection hazard	N/A	

## 3 Composition / Ingredient Data

Hazardous Components Chemical Identity	CAS Number	OSHA PEL	ACGIH TLV	Percent By Weight	EC	Average
					Number	
					231-100-4	50%
Lead	7439-92-1	50 µg/m <sup>3</sup>	50 µg/m <sup>3</sup>	45-55%	231-639-5	22%
Sulfuric Acid	7664-93-9	100 µg/m <sup>3</sup>	1.00 mg/m <sup>3</sup>	19-25%	215-174-5	21%
Lead Oxide	1309-60-0	50 µg/m <sup>3</sup>	500 µg/m <sup>3</sup>	19-23%		

	Risk Phrases	Safety Phrases
Sulphuric Acid	R61,62,20/22,33	S1/2,S26,S30,S45
Lead Oxide	R35	None

#### **4 First Aid Measures**

Contact with skin: Remove contaminated clothing immediately and drench affected skin with plenty of water, then wash with soap and water.

Contact with eyes: If substance has got into eyes, immediately wash out with plenty of water for at least 15 minutes.

Seek immediate medical attention.

Ingestion: Do not induce vomiting.

Seek immediate medical attention.

Inhalation: Remove patient to fresh air.  
Seek medical attention if irritation persists.

#### **5 Fire-Fighting Measures**

Auto-ignition point (Hydrogen) 580° C at 760 mm Hg  
Wear positive-pressure breathing apparatus  
In case of fire use foam, carbon dioxide or dry agent (S43)  
Flash point Hydrogen 259°C  
Flammable Limits in air, Lower 4.1%  
% by 3/4 vol. (Hydrogen)

Fire/explosion  
Hydrogen and oxygen gases are produced in the cells during normal battery operation (hydrogen is flammable and oxygen supports combustion).

#### **6 Accidental Release Measures**

Immediate Actions: Shut off all ignition sources  
Clean Up Actions: Neutralise with soda ash  
Place in appropriate container  
Ventilate area  
Do not empty into drains (S29)

#### **7 Handling and Storage**

Under normal conditions of battery use, internal components will not present a health hazard

Handling: Keep away from heat and sources of ignition  
Wash hands thoroughly after use  
Avoid sparks  
Avoid contact with metal jewellery and watches etc.  
Do Not Remove Vent Caps  
Do not double stack industrial batteries, it may cause damage.

Storage: Keep in cool and dry & Protect from heat.  
Store lead acid batteries with adequate ventilation.  
Room ventilation is required for batteries utilised for standby power generation.  
Never re-charge batteries in an unventilated, enclosed space.

## 8 Exposure Controls / Personal Protection

Personal protection: Wear safety shoes with toe protector.  
Where internal components are liberated use rubber or neoprene boots.  
Wear goggles/safety glasses giving complete eye protection.  
Respiratory protection may be required under exceptional circumstances when excessive air contamination exists.  
Wear PVC mitts, gloves or gauntlets.

Exposure Limits: Lead OES / LTEL - ppm 0.15 mg/m<sup>3</sup>  
Lead Dioxide OES / LTEL - ppm 0.15 mg/m<sup>3</sup>

## 9 Physical and Chemical Properties

Odour: Not applicable  
Appearance: Sealed Valve Regulated lead Acid Battery  
State under normal temp: Solid  
Flash point (Hydrogen):259° C

Internal components  
pH - (Sulphuric acid): 1.3 .  
Boiling point: Battery Electrolyte 110° C, Lead 1755° C  
(at 760 mm/Hg)  
Melting point: Lead 327.4° C  
Vapour pressure: 11.7  
Vapour density: Battery Electrolyte 3.4, (air =1)  
Specific gravity: Battery Electrolyte 1.3 g/cm<sup>3</sup>. (water =1)  
Auto-ignition point: 580° deg C at 760 mm/Hg.  
Water solubility: Battery Electrolyte is 100% soluble in water

## 10 Stability and Reactivity

VRLA Batteries are considered stable at normal conditions.  
Keep away from heat and sources of ignition.  
Incompatible with reducing agents. Incompatible with organic agents.  
Decomposition products may include hydrogen.  
Decomposition products may include sulphur oxides.

## 11 Toxicological Information

Danger of cumulative effects. (R33)  
May cause severe irritation.  
May cause gastro-intestinal disturbances.  
Can cause damage to the mucous membranes.

## 12 Ecological Information

Ecotoxicology - no information available

### **13 Disposal Considerations**

Classification: This material and/or its container must be disposed of as hazardous waste.  
Disposal considerations: Do not discharge into drains or the environment, dispose to an authorised waste collection point.

### **14 Transport Information**

**YHI POWER** battery is not regulated for transportation because it has been tested and passed the tests specified in 49 CFR 173.159(d), IATA Packing Instruction A67, and IMDG Special Provision 238.

We hereby certify that YHI POWER range of Maintenance Free Rechargeable Sealed Lead Acid batteries conform to the UN2800 classification as " Batteries, Non-Spillable, and electric storage" as a result of passing the Vibration and Pressure Differential Test described in DOT [ 49 CFR 173.159(d) and IATA/ICAO [Special Provision A67 ].

YHI POWER having met the related conditions are EXEMPT from hazardous goods regulations for the purpose of transportation by DOT,IMDG and IATA/ICAO, and therefore are unrestricted for transportation by any means.

### **15 Regulatory information**

Classification and labeling. Not classified as hazardous for supply

### **16 Other Information**

Under normal conditions of battery use, internal components will not present a health hazard. The information contained in this Safety Data Sheet is provided for battery electrolyte (acid) and lead, for exposure that may occur during battery production or container breakage or under extreme heat conditions such as fire.

Tested as per IMDG Amendment. 35-10, special provision 238 "a" and "b", Comply.

This Safety Data Sheet and the information therein does not constitute the user's own assessment of work place risk as required by other Health & Safety legislation.