

# **Bosch SMT Series** 31-1000 – Mega Power / Calcium, Calcium Technology

### Applications

Heavy Commercial Vehicles

### **Bosch Master Data**

Short Order Part Number	Bosch 13 Digit Part Number	EAN Barcode
31-1000	0092S37462HH0	4047025524339
Product Series	Technology	Warranty Period
SMT Mega Power	Calcium, Calcium Maintenance Free (MF)	Refer www.boschaftermarket.com.au
		Refer www.boschaftermarket.co.nz
Technical Information		
Nominal Voltage	Nominal Capacity (20HR)	Reserve Capacity
12V	100 AH	160 Mins
Cold Cranking Amperes (CCA)		
1000 Amps		
1000 Amps Case Size Dimension		
	Width	Container Height
Case Size Dimension	Width 173mm (6.81 inches)	Container Height 217mm (8.54 inches)
Case Size Dimension		-
Case Size Dimension Length 330mm (13 inches)		-
Case Size Dimension Length 330mm (13 inches) Total Height (with Terminal) 240mm (9.40 inches)	173mm (6.81 inches)	217mm (8.54 inches)
Case Size Dimension Length 330mm (13 inches) Total Height (with Terminal) 240mm (9.40 inches) Approx Weight (Gross)	<b>173mm (6.81 inches)</b> Terminal	217mm (8.54 inches) Grid
Case Size Dimension Length 330mm (13 inches) Total Height (with Terminal) 240mm (9.40 inches)	173mm (6.81 inches)	217mm (8.54 inches)
Case Size Dimension Length 330mm (13 inches) Total Height (with Terminal) 240mm (9.40 inches) Approx Weight (Gross)	<b>173mm (6.81 inches)</b> Terminal	217mm (8.54 inches) Grid

Rated Capacity

Mins @ 25A = 160 (20hr, 1.75V/cell, 26.7°C/80°F) = 100 AH Nominal Operating Temp. Range

25°C/77°F

Operating Temp. Range

Discharge: -30~60°C (-22~140°F)

Self Discharge


2.9mΩ

Refer chart

Internal Battery Resistance

## Product Dimension & Design


G (Standard)



## Product Performance Overview

#### Depth of Discharge Cycling Test

#### **Discharge Characterestics Test**



Your address for genuine Bosch quality:

Dealer stamp here: